

# dipper-T Water Level Meter

## Now with drawDown Mode

Length options: 50ft/15m to 2000ft/600m Warranty: 5 years, probe 1 year

The dipper-T water level meter is a topline, top quality instrument used for measuring static and falling head levels in wells and boreholes. With a touch of a button the unit changes from static to drawDown mode; a dual function unit at an affordable price.

The dipper-T in static mode is used for measuring the depth of water in wells, boreholes and standpipes. The dipper-T in drawDown mode may be used for measuring falling water levels during purging, well development and for low flow sampling; helping to protect your pumps from damage caused by dry running.



#### Features included with the dipper-T:

- Electronic Module (IP65) mode selectable for static and drawDown levels, removable for easy cleaning and servicing
- Probe (IP68) fully pressure/depth rated, field replaceable for optional casing or bottom detector probes
- Steel Tape high tensile steel, jacketed with polyethylene, high break strength, stretch resistant and lifelong legibility
- Padded Carry Case to protect your precision
  water level meter from the elements
- Tape Guide And Hanger to support the meter at the well head and to protect the tape from sharp edges on the well casing
- Vinyl Holding Grip molded to the frame, ergonomic easy grip
- Winding Handle custom made for easy rewinding with gloved hands

#### **Available options:**

- Narrow 3/8 inch probe (not removable)
- Well depth indicator probe
- Well casing indicator probe
- Potable Water only model

www.heroninstruments.com




### **WATER LEVEL METERS**

SELECTION GUIDE:			Tape (see below for details)	drawDown Electronics	Fully Submersible Probe	Field Replaceable Probe	3/8" Narrow Probe Available (not detachable)	Tape Guide and Hanger	Audio/Visual Sensor	9 Volt Battery	Temperature	Padded Carry Case	Cloth Carry Case	5 Year Product and 1 Year Probe Warranty *	3 Year Product and 1 Year Probe Warranty *	Tape Lengths**
WATER LEVEL METERS		dipper-T	A	•	•	•	•	•	•	•		•		•		50ft/15m to 1000ft/300m
		Water Tape	С		•		•	•	•	•			•		•	100ft/30m to 1000ft/300m
		Little Dipper	A	•	•	•	•	•	•	•		•			•	75ft / 22m
		skinny Dipper	С					•	•	•			•		•	100ft/30m to 500ft/150m
		mega reel	Α	•	•	•	•		•	•		•			•	1500ft/400m and up
			С		•		•		•	•						
CONDUCTIVITY/ TEMPERATURE WATER LEVEL METERS	data y la	Conductivity Plus	A		•	•		•	•	•	•	•			•	100ft/30m to 1000ft/300m
		Temperature Meter	В		•	•		•	•	•	•	•			•	100ft/30m to 500ft/150m

<sup>\*</sup> Warranties cover manufactured defect.









A = High tensile steel tape, jacketed with polyethylene, high break strength, stretch resistant and lifelong legibility

**B** = High tensile steel tape, jacketed with heat and hydrocarbon resistant Kynar, high break strength, stretch resistant and lifelong legibility





#### **HERON INSTRUMENTS INC.**

447 Moxley Rd. SS 106 | Dundas, ON Canada L9H 5E2 | TF: 800-331-2032 | T: 905-628-4999 | info@heroninstruments.com Please visit our website **www.heroninstruments.com** for more information on the complete Heron line.

 $<sup>\</sup>ensuremath{^{**}}$  Longer tape lengths and Power Reel are available.