

### DataBank Handheld Datalogger

The DataBank is a rugged and self-contained universal meter, datalogger and power supply. Specifically designed for use with the Cyclops-7 and C-sense product lines, sensor calibration and operation are simple. The DataBank records high-frequency data which may be downloaded and graphically displayed on a pc. Sensor power is provided directly from the DataBank's internal rechargeable batteries. Alternatively, an external +12 VDC power can be used. Various sensor cable lengths are available to allow sampling at multiple depths.



### DataBank Highlights

- Stores up to 9,999 records and 16 calibrations
- Includes auto-gain function
- Simplifies sensor calibration
- Works with Cyclops-7 Submersible Sensors
- Works with C-sense pCO<sub>2</sub> Sensors

### DataBank Electrical Specifications

<b>Selectable Sensor Parameters</b>	Voltage: Software selectable 3 to 12 volts Current: 150 mA at 3V to 100 mA at 12V Warm-up Time: 0-25 seconds Gain: 1-4
<b>Inputs</b>	Input Selection: Switch; <i>Differential Voltage, Differential Current or Dual Current</i> Range: 0-5V or 0-25 mA Resolution: 12 bits Sampling Rate: 1000 Hz (bursts); groups of bursts re-averaged @ 30 Hz
<b>Outputs</b>	Two, Open Drain, up to 200 mA @ 15V max (Used primarily for gain selection)
<b>Storage</b>	Non-Volatile, 1280 Kb (9,999 records, 1 record = sensor reading, date, time and location)
<b>Current Draw</b>	Computer: <=45 mA (at full charge). Sleeping <20 uA LCD Backlight: Full power ~ 30 mA. Low Power ~ 15 mA
<b>Battery</b>	Type: NiMH rechargeable, 4.8 volts, 4,000 mA/Hr. Life: Continuous up to 70 hours (dependant on sensor/settings) <b>Note:</b> When using the DataBank with the C-sense, it is recommended that the voltage be set to 6 and the warm-up time be set to 3 minutes. Using these settings with a 5 minute sampling interval, you can expect a fully charged DataBank to collect 300 samples.
<b>Charge Time</b>	~3 hours (for a fully discharged battery; ambient @ 25 degrees C)
<b>Communications</b>	USB

### DataBank Physical Specifications

<b>Size</b>	Main body: 4.6"W x 3.2"H, x 3.4"D, Handle: 4.8" long (117mm W x 81mm H x 86 mm D, Handle: 122mm) Overall: 11"H (279 mm H) with handle, strain-relief and connector.
<b>Weight</b>	1.7 lb. (.76 kg) w/o pigtail

### Ordering Information

*All instrument packages include rechargeable NiMH batteries, PC/Power USB interface cable, AC to DC charger supply, and software.*

BASE INSTRUMENT	PART NUMBER
DataBank Handheld Datalogger	2900-199
CYCLOPS-7 CABLE OPTIONS	PART NUMBER
0.6 Meter Pigtail Cable w/ Locking Sleeve	105-0580
5 Meter Pigtail Cable w/ Locking Sleeve	105-0585
10 Meter Pigtail Cable w/ Locking Sleeve	105-0581
25 Meter Pigtail Cable w/ Locking Sleeve	105-0582
50 Meter Pigtail Cable w/ Locking Sleeve	105-0583
C-SENSE CABLE OPTIONS	PART NUMBER
0.6 Meter Pigtail Cable w/ Locking Sleeve	105-2410
5 Meter Pigtail Cable w/ Locking Sleeve	105-2411
10 Meter Pigtail Cable w/ Locking Sleeve	105-2412
25 Meter Pigtail Cable w/ Locking Sleeve	105-2413
50 Meter Pigtail Cable w/ Locking Sleeve	105-2414
DATABANK ACCESSORIES	PART NUMBER
Travel Case	142-2900
Car Charger	2900-151
External Power Option	2900-940

### Contact Us

Toll-Free : 1.877.316.8049      Address:  
Phone : 408.749.0994      1995 N. 1st Street  
Fax : 408.749.0998      San Jose, CA 95112

Email : sales@turnerdesigns.com  
Web : www.turnerdesigns.com