

Humidity and Temperature USB Datalogger

Records up to 16,000 readings for each parameter
Datalogs 16,000 Humidity and 16,000 Temperature readings with a user programmable sample rate

Features:

- Datalogs 32,000 readings (16,000 for each parameter: Humidity/Temperature)
- Dew point indication via Windows[®] software (included)
- Selectable data sampling rate: 2s, 5s, 10s, 30s, 1m, 5m, 10m, 30m, 1hr, 2hr, 3hr, 6hr, 12hr, 24hr
- User-programmable alarm thresholds for RH and Temperature
- Status Indication via Red/Yellow LED and Green LED
- Long battery life (approx. 1 year)
- Complete with 3.6V Lithium battery and Windows[®] compatible analysis software



Monitors Humidity and Temperature levels in warehouse, storage rooms, freezers, shipping vans, and water damage restoration



USB connector easily plugs into a computer for data analysis of Temperature and Humidity

| Specifications | Range | Resolution | Accuracy (%rdg+digits) |
|----------------------|--|------------|---------------------------|
| Temperature | -40 to 158°F | 0.1°F/°C | ±1.0°F (-4 to 122°F) |
| | | | ±1.8°F (all other ranges) |
| | -40 to 70°C | | ±0.5°C (-20 to 50°C) |
| | | | ±1.0°C (all other ranges) |
| Humidity | 0 to 100%RH | 0.1%RH | ±3%RH |
| Datalogging interval | 2 seconds to 24 hours | | |
| Memory | Temperature: 16,000 points; Relative Humidity: 16,000 points | | |
| Dimensions | 5.1 x 1.1 x 0.98" (130 x 30 x 25mm) | | |
| Weight | 1oz (20g) | | |

Ordering Information:

RHT10Humidity and Temperature USB Datalogger

