

Water Level Meters

Geotech ET and ETL Portable Water Level Meters

The Geotech ET and ETL Portable Water Level Meters are designed to provide reliable and accurate measurements of groundwater levels. Water level readings are conveniently taken at the top of the casing with accuracy to within $\frac{1}{100}$ of a foot.

FEATURES

- ET has an extremely durable polypropylene storage reel with rugged solid aluminum frame
- ETL is on a lightweight steel and aluminum storage reel for easy transportation and durability in the field
- Highly accurate Polyethylene coated steel tape marked in engineering or metric increments
- Field serviceable $\frac{5}{8}$ " (1.59cm) probe with stainless steel conductors for durability
- An optional $\frac{3}{8}$ " (.95cm) non-field replaceable probe is available
- Adjustable sensitivity to prevent false triggering
- Audible and visible alarms activated when the probe makes contact with water
- Easily replaced 9 volt battery
- Water resistant padded carrying case to protect instrument (optional)
- Built in reel hanger on ET models and included tape guide for longer tape life
- MDPE and ETFE coated steel tape available upon request
- Optional tape weight helps sink probe into a deep or crooked well




Geotech ETL



$\frac{5}{8}$ " (1.59cm) Field Replaceable Probe



Optional $\frac{3}{8}$ " (1cm) Probe



Optional White MDPE Tape



Geotech ET with optional bag and tape weight

SPECIFICATIONS

Size:	ET Reel	13" H x 11" W x 7" D (33cm H x 28cm W x 18cm D)
	ETL 500' Reel	14.5" H x 9" W x 11.5" D (37cm H x 23cm W x 29cm D)
	ETL 750/1000' Reel	15.75" H x 13" W x 11.5" D (40cm H x 33cm W x 29cm D)
Probe	$\frac{5}{8}$ " O.D. x $6\frac{1}{8}$ " L	(1.59cm O.D. x 15.56cm L)
	$\frac{3}{8}$ " O.D. x $6\frac{1}{2}$ " L (optional)	(1cm O.D. x 16.5cm L)
Length & Weight:	ET	100' (30 m) = 9 lbs. (4 kg)
		200' (60 m) = 11 lbs. (5 kg)
		300' (100 m) = 14 lbs. (6.3 kg)
	ETL	500' (150 m) = 20 lbs. (9 kg)
		750' (225 m) = 24 lbs. (10.9 kg)
		1000' (300 m) = 28 lbs. (12.7 kg)
Accuracy:	ET Tape	100th of a foot / 100' (Per Federal Specification GGG-T-106E)
Material:	Reel	Polypropylene and aluminum (ET) Powder coated steel and aluminum (ETL)
	Tape	Polyethylene coated steel
	Probe	PTFE and stainless steel
Power:		9 Volt DC alkaline battery
Alarm:		Audible and visual
Warranty:		1 year
Certifications:		CE

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com