

Lufft WS503-UMB – Tilttable Pyranometer, Wind, Temperature, Air Pressure, Relative Humidity, Electronic Compass

From the WS product family of professional intelligent measurement transducers with digital interface for environmental applications.

Integrated design with ventilated radiation protection for measuring:

- Air temperature
- Relative humidity
- Air pressure
- Wind direction
- Wind speed
- Solar Radiation

Relative humidity is measured by means of a capacitive sensor element; a precision NTC measuring element is used to measure air temperature.

The world renowned technology of Kipp+Zonen CMP3 is integrated.

Ultrasonic sensor technology is used to take wind measurements.

Measurement output can be accessed by the following protocols:
UMB-Binary, UMB-ASCII, SDI-12, MODBUS.

One external temperature or rain sensor is connectable.



Tilttable Pyranometer

Ultrasonic wind sensor

Aspirated temperature/humidity measurement

Open communication protocol:

- UMB-ASCII
- UMB-Binary
- SDI-12
- MODBUS
- Analogue outputs in combination with 8160.UDAC

Third-Party-Rain gauge sensors are compatible: 0.1 mm, 0.2 mm, 0.5 mm, 1mm heated and unheated.

Lufft WS503-UMB Compact Weather Station			Order No.
WS503-UMB			8375.U11
Technical Data	Dimensions	Ø approx. 150 mm, height 392mm	
	Weight	approx. 1.5 kg	
Temperature	Principle	NTC	
	Measuring range	-50 ... 60 °C	
	Accuracy	±0.2 °C (-20 °C ... +50 °C), otherwise ±0.5 °C (>-30 °C)	
Relative humidity	Principle	Capacitive	
	Measuring range	0 ... 100 % RH	
	Accuracy	±2 % RH	
Radiation	Response time (95%)	< 18s	
	Non-stability (change/year)	< 1%	
	Non-linearity (0 to 1,000 W/m²)	< 1%	
	Directional error (at 80° with 1,000 W/m²)	< 20W/m²	
	Temperature dependence of sensitivity	< 5% (-10 bis +40 °C)	
	Tilt error (at 1000 W/m²)	< 1%	
	Spectral range (50% points)	300 to 2,800 nm	
	Measuring range	1400 W/m²	
	Altitude	0...60°	
Air pressure	Azimuth	-10° ... +10°	
	Principle	MEMS capacitive	
	Measuring range	300 ... 1200 hPa	
Wind direction	Accuracy	±0.5 hPa (0 ... +40°C)	
	Principle	Ultrasonic	
	Measuring range	0 ... 359.9°	
Wind speed	Accuracy	< 3° RMSE >1.0 m/s	
	Principle	Ultrasonic	
	Measuring range	0 ... 75 m/s	
General Information	Accuracy	±0.3 m/s or 3% (0...35 m/s) RMS of reading, whichever is greater ±5% (>35 m/s) RMS	
	Heating	20 VA at 24 VDC	8379.USP
	Protection type housing	IP66	8366.USV1
	Interface	RS485, 2-wire, half-duplex	8160.UISO
	Operating power consumption	12-24 VDC ±10%	8160.UDAC
	Operating humidity range	0 ... 100 %	8160.WT1
Accessories	Operating temperature range	-50 ... 60 °C	8160.WST1
	Surge protection		8370.UKAB20
	Power supply 24V/4A		8353.10
	UMB Interface converter ISOCON-UMB		
	Digital-analog-converter DACON8-UMB		
Temperature Sensor WT1			
Road Surface Temperature Sensor WST1			
Connection cable, 20m			
Rain Sensor WTB100			

