



## HOBO<sup>®</sup> MX1102A Data Logger

Carbon Dioxide - Temp - RH

Onset's HOBO MX1102 CO<sub>2</sub> logger makes it more convenient than ever to measure and record CO<sub>2</sub> in buildings and other non-condensing environments. It measures CO<sub>2</sub> from 0-5,000 parts per million (ppm) - and our free HOBObconnect app lets you access data right from your mobile phone, tablet, or Windows computer when within a 100-foot range of the logger.

The MX1102 also features a USB port so it can be used with a computer running HOBOWare graphing & analysis software.

Add the MX Gateway for remote access to your data in Onset's cloud-based HOBOLink software.

You can download the HOBObconnect app here:

### Key Advantages:

- Wireless communication via Bluetooth technology
- Six-month battery life at 5-minute CO<sub>2</sub> logging rate
- Easy to deploy and offload using free HOBObconnect app
- Visual and audible high & low alarm thresholds
- Self-calibrating NDIR CO<sub>2</sub> sensor technology ensures optimal accuracy and lower maintenance costs
- Patented connectivity technology



## HOBO MX1102A Data Logger Specifications

### Temperature Sensor

Range	0° to 50°C (32° to 122°F)
Accuracy	±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)
Resolution	0.024°C at 25°C (0.04°F at 77°F)
Drift	<0.1°C (0.18°F) per year

### RH Sensor

Range	1% to 90% RH (non-condensing)
Accuracy	±2% from 20% to 80% typical to a maximum of ±4.5% including hysteresis at 25°C (77°F); below 20% and above 80% ±6% typical
Resolution	0.01%
Drift	<1% per year typical

### CO<sub>2</sub> Sensor

Range	0 to 5,000 ppm
Accuracy	±50 ppm ±5% of reading at 25°C (77°F), less than 90% RH non-condensing and 1,013 mbar
Warm-up Time	15 seconds
Calibration	Auto or manual to 400 ppm
Non-linearity	<1% of FS
Pressure Dependence	0.13% of reading per mm Hg (corrected via user input for elevation/altitude)
Operating Pressure Range	950 to 1,050 mbar (use Altitude Compensation for outside of this range)
Compensated Pressure Range	-305 to 5,486 m (-1,000 to 18,000 ft)
Sensing Method	Non-dispersive infrared (NDIR) absorption

### Response Time

Temperature	12 minutes to 90% in airflow of 1 m/s (2.2 mph)
RH	1 minute to 90% in airflow of 1 m/s (2.2 mph)
CO <sub>2</sub>	1 minute to 90% in airflow of 1 m/s (2.2 mph)

### Logger

Radio Power	1 mW (0 dBm)
Transmission Range	Approximately 30.5 m (100 ft) line-of-sight
Wireless Data Standard	Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)
Logger Operating Range	0° to 50°C (32° to 122°F); 0 to 95% RH (non-condensing)
Logging Rate	1 second to 18 hours
Logging Modes	Fixed interval (normal, statistics) or burst
Memory Modes	Wrap when full or stop when full
Start Modes	Immediate, push button, date & time, or next interval
Stop Modes	When memory full, push button, date & time, or after a set logging period
Time Accuracy	± 1 minute per month at 25°C (77°F)
Power Source	4 AA 1.5 Volt batteries (user replaceable) or USB power source (5 V DC, 2 Watts)

<b>Battery Life</b>	6 months, typical with logging and sampling intervals of 5 minutes or slower; 6 months or less with logging and sampling intervals faster than 5 minutes while logging CO <sub>2</sub> . Entering burst logging mode will impact battery life. With app use, battery life can be reduced by remaining connected, excessive readouts, audible alarms, and paging. Visual/audible alarms and other events can have a marginal impact on battery life.
<b>Memory</b>	128 KB (84,650 measurements, maximum)
<b>Download Type</b>	USB 2.0 interface or via Bluetooth Smart
<b>Full Memory Download Time</b>	20 seconds via USB; approximately 60 seconds via Bluetooth Smart, may take longer the further the device is from the logger
<b>LCD</b>	LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range
<b>Size</b>	7.62 x 12.95 x 4.78 cm (3.0 x 5.1 x 1.88 inches)
<b>Weight</b>	267.4 g (9.43 oz)
<b>Environmental Rating</b>	IP50
<b>CE</b>	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).



## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
 470 MacArthur Boulevard  
 Bourne, MA 02532