

# 12 VOLT PUMP CHARTS

## STANDARD ENGINEERED PLASTIC PUMPS

### PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	OPTIONAL CONTROLLER	3	10	20	25	30	40	50	55	60	70	85	90
<b>CYCLONE</b> with 35' of wire	P-10100	LOW FLOW SAMPLING CONTROLLER (PA-10800)	2.0 G.P.M 12V.	1.0 G.P.M 12V.	.35 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>MINI-TYPHOON</b> with 50' of wire	P-10150	LOW FLOW SAMPLING CONTROLLER (PA-10800)	2.5 G.P.M 12V.	2.2 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A
<b>TYPHOON</b> with 60' of wire	P-10200	LOW FLOW SAMPLING CONTROLLER (PA-10800)	3.0 G.P.M 12V.	2.3 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.6 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A
<b>TEMPEST / TWISTER</b> with 70' of wire	P-10250	LOW FLOW SAMPLING CONTROLLER (PA-10800)	3.2 G.P.M 12V.	2.8 G.P.M 12V.	2.2 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.2 G.P.M 12V.	.75 G.P.M 12V.	.60 G.P.M 12V.	.40 G.P.M 12V.	N/A	N/A	N/A
<b>MINI-MONSOON</b> with 80' of wire	P-10300	LOW FLOW SAMPLING CONTROLLER (PA-10800)	4.0 G.P.M 12V.	3.2 G.P.M 12V.	2.8 G.P.M 12V.	2.5 G.P.M 12V.	2.2 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.75 G.P.M 12V.	.60 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A
<b>TORNADO</b> with 90' of wire	P-10330	LOW FLOW SAMPLING CONTROLLER (PA-10800)	4.25 G.P.M 12V.	3.75 G.P.M 12V.	3.5 G.P.M 12V.	3.25 G.P.M 12V.	3.0 G.P.M 12V.	2.5 G.P.M 12V.	1.75 G.P.M 12V.	1.25 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.35 G.P.M 12V.	N/A

PUMP MODEL	ITEM NO.	OPTIONAL CONTROLLER	10	20	40	60	80	100	120	140	160	180	200	220
<b>ABYSS</b> with 230' of wire	P-10380	LOW FLOW SAMPLING CONTROLLER (PA-10800)	1.15 G.P.M 12V.	1.0 G.P.M 12V.	1.0 G.P.M 12V.	.85 G.P.M 12V.	.85 G.P.M 12V.	.80 G.P.M 12V.	.80 G.P.M 12V.	.75 G.P.M 12V.	.75 G.P.M 12V.	.70 G.P.M 12V.	.70 G.P.M 12V.	.50 G.P.M 12V.

## WATER SPOUT ENGINEERED PLASTIC PUMPS

### PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	OPTIONAL CONTROLLER	3	10	20	25	30	40	50	55	60	70	85	90
<b>WATER SPOUT 1 TOP INLINE PUMP</b> 1-Stage, with 3' of wire*	P-10000	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>WATER SPOUT 1 DOUBLE BOTTOM BOOSTER</b> 2-Stage, with 3' of wire*	P-10010	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>WATER SPOUT 1 COMPLETE</b> with 50' of wire	P-10020	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	2.5 G.P.M 12V.	2.2 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A
<b>WATER SPOUT 2 COMPLETE</b> with 70' of wire	P-10050	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	3.2 G.P.M 12V.	2.75 G.P.M 12V.	2.5 G.P.M 12V.	2.25 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A

\*Pump cannot be used by itself.

Pump test results were conducted with a 12.5 volt source.

DTW means Depth-To-Water. Specifications subject to change without notice.

## HIGH PERFORMANCE ENGINEERED PLASTIC PUMPS

PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	REQUIRED CONTROLLERS	10	20	40	50	70	80	85	100	110	120	140	150	180	200
<b>MEGA-TYPHOON</b> with 90' of wire	P-10350	POWER BOOSTER 1 (PA-10600) OR LOW FLOW WITH POWER BOOSTER 1(PA-10650)	3.5 G.P.M 12V.	3.1 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	.5 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>SUPER TWISTER</b> with 90' of wire	P-10275	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	2.5 G.P.M 12V.	2.0 G.P.M 12V.	1.50 G.P.M 12V.	1.25 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.50 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>Tsunami</b> with 110' of wire	P-10400	POWER BOOSTER 2 (PA-10700) OR LOW FLOW WITH POWER BOOSTER 2 (PA-10750)	4.0 G.P.M 12V.	3.8 G.P.M 12V.	3.2 G.P.M 12V.	3.0 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.50 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A
<b>MONSOON</b> with 130' of wire	P-10500	POWER BOOSTER 2 (PA-10700) OR LOW FLOW WITH POWER BOOSTER 2 (PA-10750)	4.4 G.P.M 12V.	4.2 G.P.M 12V.	3.5 G.P.M 12V.	2.8 G.P.M 12V.	2.1 G.P.M 12V.	1.9 G.P.M 12V.	1.6 G.P.M 12V.	1.5 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	N/A	N/A	N/A	N/A
<b>HURRICANE</b> with 160' of wire	P-10510	POWER BOOSTER 2 (PA-10700) OR LOW FLOW WITH POWER BOOSTER 2 (PA-10750)	4.5 G.P.M 12V.	4.0 G.P.M 12V.	3.0 G.P.M 12V.	2.75 G.P.M 12V.	2.25 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.35 G.P.M 12V.	1.25 G.P.M 12V.	1.15 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A
<b>MEGA-MONSOON</b> with 210' of wire	P-10520	LOW FLOW WITH POWER BOOSTER 3 (PA-10850)	4.0 G.P.M 12V.	3.75 G.P.M 12V.	2.75 G.P.M 12V.	2.5 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.75 G.P.M 12V.	1.65 G.P.M 12V.	1.65 G.P.M 12V.	1.5 G.P.M 12V.	.65 G.P.M 12V.	.50 G.P.M 12V.	.30 G.P.M 12V.	.15 G.P.M 12V.

## STAINLESS STEEL (SS) PUMPS

PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	REQUIRED CONTROLLER	10	20	30	40	60	70	80	100	110	120	130	150
<b>SS-MINI MONSOON</b> with 90' of wire	PS-10405	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	1.75 G.P.M 12V.	1.25 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A
<b>SS-MEGA-TYPHOON</b> with 90' of wire	PS-10350	LOW FLOW WITH POWER BOOSTER 1 "LCD" CONTROLLER (PA-10660)	3.0 G.P.M 12V.	2.75 G.P.M 12V.	2.55 G.P.M 12V.	2.0 G.P.M 12V.	1.0 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A
<b>SS-MONSOON</b> with 130' of wire	PS-10400	LOW FLOW WITH POWER BOOSTER 2 "LCD" CONTROLLER (PA-10670)	3.5 G.P.M 12V.	3.25 G.P.M 12V.	3.0 G.P.M 12V.	3.0 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A
<b>SS-HURRICANE</b> with 160' of wire	PS-10415	LOW FLOW WITH POWER BOOSTER 2.5 "LCD" CONTROLLER (PA-10675)	3.5 G.P.M 12V.	3.25 G.P.M 12V.	3.0 G.P.M 12V.	3.0 G.P.M 12V.	2.5 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.25 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	.85 G.P.M 12V.	.50 G.P.M 12V.



Pump test results were conducted with a 12.5 volt source.

DTW means Depth-To-Water . Specifications subject to change without notice.