

SL-86-911-TP

Mountable Keyboard with Touchpad

The SL-86-911-TP keyboard is designed for vehicle mount in emergency, police, service, transport trucks and marine vessels. Features include a user-friendly integrated touchpad, backlit keys for low-light environments, a one-touch emergency key and mounting holes. The new, easy-to-use integrated touchpad was created to meet public demand for a user-friendly alternative to the traditional HulaPoint™ device.



Technical Specifications

Certifications

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

Key Switch

MATERIAL: Industrial Silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.055" (1.4mm)
ACTUATION FORCE: 200g (+/-20g)
FEEDBACK: Tactile with mechanical snap

Power

KEYBOARD: 5V@10ma (from CPU port)
TOUCHPAD: 5V@6ma (from mouse conn. port)

Temperature Range

Storage -40C to +65C
Operating 0C to + 60C

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

Weight

3 lbs (1.38 kg)

Dimensions

11.4" x 7.3" x 1.86" (w-h-d)
289.56mm x 185.42mm x 47.24mm

Cable

LENGTH: 4 ft coiled (1.2m)
DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB

Compatibility

PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS

Warranty

1 Year Limited Warranty

Model Numbers

SL-86-911-TP-PS2: With PS/2 cable
SL-86-911-TP-USB: With USB cable

Features and Benefits

- 11.4" x 7.3" x 1.86" (w-h-d)
- Red Backlit Keys
- 86-Key Functionality
- Fn Key for Secondary Legend Flexibility
- Integrated Touchpad
- Meets NEMA 4X (IP65) Specifications
- Mobile Mounting Holes
- One-Touch Emergency Key