

Material Safety Data Sheet

NCL of Wisconsin, Inc.
PO Box 8
Biramwood, WI 54414
Emergency Telephone No: 800-424-9300 (Chemtrec)

Date of this revision: 11-02-2004

Product Identification

Product Name: YSI 3841 Ammonium Standard, 1 ppm as N
Synonyms: None. Molecular Weight: NA
Chemical Name: NA Chemical Family: NA
Product CAS#: NA Formula: NA

Ingredients

- | | |
|---|----------------------------------|
| 1. Ammonium chloride | CAS# 12125-02-9 |
| Percent: <1 | SARA: Not Listed. |
| TLV: 10 mg/m ³ . | PEL: 10 mg/m ³ |
| Hazard: Moderately toxic – May cause irritation | |
| 2. Lithium Acetate, Dihydrate | CAS# 6108-17-4 |
| Percent: <1 | SARA: Not listed |
| TLV: Not established. | PEL: Not established |
| Hazard: Moderately toxic – May cause irritation | |
| 3. Sodium Azide | CAS# 26628-22-8 |
| Percent: <0.01 | SARA: Not listed. |
| TLV: 100 ppb Ceiling | PEL: 0.3 ppm as NaN ₃ |
| Hazard: Extremely toxic – Explosion Hazard | |
| 4. Hydrochloric Acid | CAS# 7647-01-0 |
| Percent: <0.01 | SARA: Listed. |
| TLV: 5 ppm ceiling | PEL: 5 ppm ceiling |
| Hazard: Causes burns. | |
| 5. Deionized water | CAS# 7732-18-5 |
| Percent: >98.8 | SARA: Not listed |
| TLV: Not applicable. | PEL: Not applicable. |
| Hazard: None. | |

Precautionary Measures

Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Minimal contact, as with all chemicals, is a good policy to follow.

Emergency/First Aid

In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes. If swallowed, induce vomiting by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person. In all cases, call a physician.

DOT Hazard Class: Not Regulated

Appearance: Clear colorless solution.
 Odor: Odorless
 Solubility: Infinitely soluble in water.
 Boiling Point: 100° C (212° F)
 Melting Point: 0° C (32° F)
 Specific Gravity: 1.0
 Vapor Density (Air=1): Essentially the same as water.
 Vapor Pressure (mm Hg): Essentially the same as water.
 Evaporation Rate: Essentially the same as water.

.....
 Fire and Explosion
 Information

Section Two

Fire: Not considered to be a fire hazard.
 Explosion: Not considered to be an explosion hazard
 Fire Extinguishing Media: Use any suitable means for extinguishing surrounding fire.

.....
 Reactivity Data

Section Three

Stability: Stable under ordinary conditions of use and storage
 Hazardous Decomposition Products: Involvement in a fire causes decomposition to form hydrogen chloride and ammonia.
 Hazardous Polymerization: This substance does not polymerize.
 Incompatibilities: Concentrated acids, strong bases, silver salts, potassium chlorate, ammonium nitrate, bromine trifluoride, and iodine heptafluoride.

.....
 Leak/Spill/Disposal
 Information

Section Four

Flush to sewer with large amounts of water.
 Ensure compliance with Federal, State, and local regulations
 Reportable Quantity: 5000 lbs.

.....
 Health Hazard Information

Section Five

A. Exposure/Health Effects

Inhalation: No information found.
 Ingestion: large doses may cause nausea, vomiting, and acidosis. Target organs: Kidneys, Central nervous system, bone marrow.
 Skin Contact: Prolonged contact may cause skin irritation.
 Eye Contact: May cause redness and pain.
 Chronic Exposure: Cumulative poison (lithium ion) may cause damage to central nervous system. Lithium compounds have been implicated in the development of aplastic anemia.
 Cancer information: No information found for any ingredient.
 Aggravation of Pre-existing Conditions: No information found.

B. First Aid

Ingestion: If swallowed, induce vomiting by giving two glasses of water and sticking finger down throat. Never give anything to an unconscious person. Get medical attention immediately.
 Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
 Skin Exposure: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing. Get medical attention if irritation develops or persists.
 Eye Exposure: Wash eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Ventilation System: In general, dilution ventilation is a satisfactory health hazard control for this material. However, if conditions of use create discomfort to a worker, a local exhaust should be considered.

Personal Respirators (NIOSH Approved): For conditions of use where exposure to mist exists, a dust/mist respirator may be worn. For emergencies, a self-contained breathing apparatus may be necessary.

Skin Protection: Rubber gloves and lab coat, apron or overalls.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Contact lenses should not be worn when working with this material.

Maintain eye-wash fountain and quick-drench facilities in work areas.

Keep in a tightly closed container. Protect container from physical damage and direct sunlight.

The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, NCL of Wisconsin, Inc. makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular purpose. Accordingly, NCL of Wisconsin, Inc will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS.

END OF MATERIAL SAFETY DATA SHEET